

Tapware is to be installed by a Licensed Plumber in accordance with AS/NZS 3500:2003

Recommended working water pressure 300-500 kpa.
Maximum water temperature is 65 deg.c.

INSTALLATION GUIDE

Circa Basin Sink Hob Mixer Set


Product code: CIR-15 Available options: Basin Sink Hob Mixer Set

ROUGH IN PLUMBING

- Mixer clearance hole in mounting surface must be between 45-50mm.
- Outlet clearance hole is to be between 22-28mm.
- Maximum bench thickness 32mm.
- A Pressure Plug is provided to seal one of the Outlet Ports.
- Fit the supplied 1/2" male fittings with the appropriate thread tape or sealant to Mixer Body.
- Working from under the bench top, fit the Hob Mixer and secure using the fixing screws as shown.
- Ensure the Mixer is aligned square to the bench to allow for proper Handle position.
- Fit and tighten the Flexible hoses to the Hot/ Cold Ports and Outlet Port.

DRESS FINISHING

- Apply sealant around the Mixer Body to ensure the finished surface is water-tight.
- Fit the Dress Ring onto the Mixer Body.
- Fit the Handle Body onto the Mixer Cartridge lever. Ensure The Handle Body is fully engaged.
- Tighten the Set screw of the Handle Body using the 2.5mm Allen Key provided. (Tighten Well)
- Insert Outlet through clearance hole in mounting surface.
- Ensure the "Front label is positioned to face the operator.
- Working from under the mounting surface fit the plastic washer and locknut to the thread of the Outlet.
- Tighten Outlet well, ensure the FRONT label remains in position.
- Connect Flexible Hose from Hob Mixer to Outlet.
- Once all connections are made, test Mixer and Outlet function.
- Check for Leaks.



PLUMBER NOTE

- On-site high pressure line testing must be conducted with Mixer in the closed position. (STATIC TEST ONLY)
- Under no circumstances is the Mixer to be opened when exceeding the maximum stated water pressure.
- At the completion of testing, do not relieve any high pressure by opening the Mixer.
- Exposing the internals of the Mixer Cartridge to higher than specified water pressures will void the warranty.